

Network Working Group	T. Hansen, Ed.
Internet-Draft	AT&T Laboratories
Intended status: Informational	L. Masinter
Expires: September 26, 2015	M. Hardy
	Adobe
	March 25, 2015

PDF for an RFC Series Output Document Format

draft-hansen-rfc-use-of-pdf-07

Abstract

This document discusses options and requirements for the PDF rendering of RFCs in the RFC Series, as outlined in RFC 6949. It also discusses the use of PDF for Internet-Drafts, and available or needed software tools for producing and working with PDF.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 26, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. **Introduction**
2. **Options and Requirements for PDF RFCs**
 - 2.1. **"Visible" Requirements**
 - 2.1.1. **General Visible Requirements**
 - 2.1.2. **Page Size, Margins**
 - 2.1.3. **Headers and Footers**
 - 2.1.4. **Paragraph Numbering**
 - 2.1.5. **Paged Content Layout Quality**
 - 2.1.6. **Similarity to Other Outputs**
 - 2.1.7. **Typeface Choices**
 - 2.1.8. **Hyphenation and Line Breaks**
 - 2.1.9. **Hyperlinks**
 - 2.2. **"Invisible" Options and Requirements**
 - 2.2.1. **Internal Text Representation**
 - 2.2.2. **Unicode Support**
 - 2.2.3. **Image Processing (Artwork)**
 - 2.2.4. **Text Description of Images (Alt-Text)**
 - 2.2.5. **Metadata Support**
 - 2.2.6. **Document Structure Support**
 - 2.2.7. **Tagged PDF**
 - 2.2.8. **Embedded Files**
 - 2.3. **Digital Signatures**
3. **Choosing PDF versions and Standards**
4. **References**
 - 4.1. **References**
 - 4.2. **Informative References**
- Appendix A. History and Current Use of PDF with RFCs and Internet-Drafts**
 - A.1. **RFCs**
 - A.2. **Internet-Drafts**
- Appendix B. Tooling**
 - B.1. **PDF Viewers**
 - B.2. **Printers**
 - B.3. **PDF Generation Libraries**
 - B.4. **Typefaces**
 - B.5. **Other Tools**
- Appendix C. Additional Reading**
- Appendix D. Acknowledgements**
- Authors' Addresses**

1. Introduction

The RFC Series is evolving, as outlined in [\[RFC6949\]](#). Future documents will use an canonical format, XML, with renderings in various formats, including PDF.

Because PDF has a wide range of capabilities and alternatives, not all PDFs are "equal". For example, visually similar documents could consist of scanned or rasterized images, or include text layout options, hyperlinks, embedded fonts, and digital signatures. (See

https://en.wikipedia.org/wiki/Portable_Document_Format for a history of PDF. Also see

<https://en.wikipedia.org/wiki/PDF/A> and <https://en.wikipedia.org/wiki/PDF/UA> for descriptions of PDF/A and PDF/UA, respectively.)

This document explains some of the relevant options and makes recommendations, both for the RFC series

and Internet-Drafts.

The PDF format and the tools to manipulate it are not as well known as those for the other RFC formats, at least in the IETF community. This document discusses some of the processes for creating and using PDFs using both open source and commercial products.

NOTE: see <https://github.com/masinter/pdfRFC> for XML source, related files, and an issue tracker for this document.

2. Options and Requirements for PDF RFCs

This section lays out options and requirements for PDFs produced by the RFC editor for RFCs. There are two sections: "Visible" options are related to how the PDF appears when it is viewed with a PDF viewer. "Internal Structure" options affect the ability to process PDFs in other ways, but do not control the way the document appears. (Of course, a viewer UI might display processing capabilities, such as showing if a document has been digitally signed.)

In many cases, the choice of PDF requirements is heavily influenced by the capabilities of available tools to create PDFs. Most of the discussion of tooling is to be found in [Appendix B](#).

NOTE: each option in this section will eventually outline the nature of the design choice, outline the pros and cons, and make a recommendation.

2.1. "Visible" Requirements

PDF supports rich visible layout of fixed-sized pages.

2.1.1. General Visible Requirements

For a consistent "look" of RFC and good style, the PDFs produced by the RFC editor should have a clear, consistent, identifiable and easy-to-read style. They should print well on the widest range of printers, and look good on displays of varying resolution.

2.1.2. Page Size, Margins

PDF files are laid out for a particular size of page and margins. There are two paper sizes in common use: "US Letter" (8.5 x 11 inches, 216x279 mm, in popular use in North America) and "A4" (210x297 mm, 8.27x11.7 inches, standard for the rest of the world). Usually PDF printing software is used in a "shrink to fit" mode where the printing is adjusted to fit the paper in the printer. There is some controversy, but the argument that A4 is an international standard is compelling.

Recommendation: The Internet-Draft and RFC processors should produce A4 size by default. However, the margins and header positioning will need to be chosen to look good on both paper sizes using common printing methods.

2.1.3. Headers and Footers

Page headers and footers are part of the page layout. There are a variety of options. Note that page headers and footers in PDF can be typeset in a way that the entire (longer) title might fit.

Recommendation: Page headers and footers should contain similar information as the headings in the current text versions of documents, including page numbers, title, author, working group. However, the page headers and footers should be typeset in a way so as to be inobtrusive. The page headers and footers should be placed into the PDF in a way not to interfere with screen readers.

2.1.4. Paragraph Numbering

One common feature of the Internet-draft output formats are optional visible paragraph numbers, to aid in discussions. In the PDF and thus printed rendition, it is possible to make paragraph numbers unobtrusive, and even to impinge on the margins.

Recommendation: When the XML "editing=yes" option has been chosen, show paragraph numbers in the right margin, typeset in a way so as to be inobtrusive. (The right margin instead of the left margin prevents the paragraph numbers from being confused with the section numbers.) If possible, the paragraph numbers should be coded in a way that they do not not interfere with screen readers.

2.1.5. Paged Content Layout Quality

The process of creating a paged document from running text typically involves insuring that related material is present on the same page together, and that artifacts of pagination don't interfere with easy reading of the document. Typical high-quality layout processors do several things:

Widow and Orphan Management:

Widows and orphans (https://en.wikipedia.org/wiki/Widows_and_orphans) should be avoided automatically (unless the entire paragraph is only one line). Insure that a page break does not occur after the first line of a paragraph (orphans), if necessary, using slightly longer page sizes. Similarly, insure that a page break does not occur before the last line of a paragraph (widows).

Keep Section Heading Contiguous:

Do not page break immediately after a section heading. If there isn't room on a page for the first (two) lines of a section after the section heading, page break before the heading.

Avoid Splitting Artwork:

Figures should not be split from figure titles. If possible, keep the figure on the same page as the (first) mention of the figure.

Headers for Long Tables after Page Breaks:

Another common option in producing paginated documents is to include the column headings of a table if the table cannot be displayed on a single page. Similarly, tables should not be split from the table titles.

keepWithNext and keepWithPrevious:

The XML attributes of "keepWithNext" and "keepWithPrevious" should be followed whenever possible.

Whitespace Preservation:

The XML entities such as NBSP and NBHYPHEN should be followed as directed whenever possible.

Layout engines differ in the quality of the algorithms used to automate these processes. In some cases, the automated processes require some manual assistance to insure, for example, that a text line intended as a heading is "kept" with the text it is heading for.

Recommendation: Choose a layout engine so that manual intervention is minimized, and that widow and orphan processing, heading and title contiguation are automatic.

2.1.6. Similarity to Other Outputs

There is some advantage to having the PDF files look like the text or HTML renderings of the same document. There are several options even so. The PDF

1. could look like the text version of the document, or
2. could look like the text version of the document but with pictures rendered as pictures instead of using their ASCII-art equivalent, or
3. could look like the HTML version.

Recommendation: the PDF rendition should look like the HTML rendition, at least in spirit. Some differences from the HTML rendition would include different typeface and size (chosen for printing), page numbers in the

table of contents and index, and the use of page headers and footers.

Most of the choices used for the HTML rendering are thus applicable:

TBA

Most of the choices used for the CSS rendering are also applicable:

TBA

2.1.7. Typeface Choices

A PDF may refer to a font by name, or it may use an embedded font. When a font is not embedded, a PDF viewer will attempt to locate a locally installed font of the same name. If it can not find an exact match, it will find a "close match". If a close match is not available, it will fall back to something implementation dependent and usually undesirable.

In addition, the PDF/A standards mandate the embedding of fonts. Preferably, the software generating the files would produce PDF/A-conforming files directly, thus ensuring that all glyphs include Unicode mappings and embedded fonts from the outset.

If the HTML version of the document is being visually mimicked, the font(s) chosen should have both variable width and constant width components, as well as bold and italic representations.

The typefaces used by Internet-Drafts and by RFCs need not be identical.

Few fonts have glyphs for the entire repertoire of Unicode characters; for this purpose, the PDF generation tool may need a set of fonts and a way of choosing them. The RFC Editor is defining where Unicode characters may be used within RFCs. [\[I-D.flanagan-nonascii\]](#)

Typefaces are typically licensed and, in many cases, there is a fee for use by PDF creation tools; however, not for display or print of the embedded fonts.

Recommendations:

- Recommendation: for consistent viewing, all fonts should be embedded. The fonts used must be available for use by the IETF community.
- The choice of type faces with respect to serif, sans serif, monospace, etc., should follow the recommendations for HTML and CSS rendering [\[I-D.hildebrand-html-rfc\]](#).
- The range of Unicode characters allowed in the XML source for Internet-Drafts and RFCs may be bounded by the availability of embeddable fonts with appropriate glyphs [\[I-D.flanagan-nonascii\]](#).

2.1.8. Hyphenation and Line Breaks

Typically, when doing page layout of running text, especially with narrow page width and long words, layout processors of English text often have the option of hyphenating words, or using existing hyphens as a place to introduce word breaks. However, line breaks mid-word where the "word" is actually technically a sequence of characters representing a protocol element or protocol sequence is actively harmful.

Recommendation: avoid introducing hyphenated line breaks mid-word into the visual display, consistent with requirements for plain text and HTML.

2.1.9. Hyperlinks

PDF supports hyperlinks both to sections of the same document and to other documents.

The conversion to PDF can generate:

- hyperlinks within the document
- hyperlinks to other RFCs and Internet-Drafts
- hyperlinks to external locations
- hyperlinks within a table of contents
- hyperlinks within an index

One question that must be answered is where should hyperlinks to RFCs point? To the info page for the RFC? To the PDF version of the RFC?

Similar questions need to be answered on references to Internet-Drafts: Where should hyperlinks to Internet-Drafts point? To the datatracker entry? To the tools entry? To a PDF version of the Internet-Draft?

Recommendations:

- All hyperlinks available in the HTML rendition of the RFC should also be visible and active in the PDF produced. This includes both internal hyperlinks and hyperlinks to external resources.
- The table of contents, including page numbers, are useful when printed. These should also be hyperlinked to their respective sections.
- Hyperlinks to RFCs from the references section should point to the RFC "info" page, which then links to the various formats available.
- Hyperlinks to Internet-Drafts from the references section should point to the datatracker entry page for the draft, which then links to the various formats available.

2.2. "Invisible" Options and Requirements

PDF offers a number of features which improve the utility of PDF files in a variety of workflows, at the cost of extra effort in the xml2rfc conversion process; the tradeoffs may be different for the RFC editor production of RFCs and for Internet-Drafts.

2.2.1. Internal Text Representation

The contents of a PDF file can be represented in many ways. The PDF file could be generated:

- as an image of the visual representation, such as a JPEG image of the word "IETF". That is, there might be no internal representation of letters, words or paragraphs at all.
- placing individual characters in position on the page, such as saying "put an 'F' here", then "put an 'T' before it", then "put an 'E' before that", then "put an 'I' before that" to render the word "IETF". That is, there might be no internal representation of words or paragraphs at all.
- placing words in position on the page, such as keeping the word "IETF" would be kept together. That is, there might be no internal representation of paragraphs at all.
- insuring that the running order of text in the content stream matches the logical reading order. That is, a sentence sentence such as 'The Internet Engineering Task Force (IETF) supports the Internet.' would be kept together as a sentence, and multiple sentences within a paragraph would be kept together.

All of these end up with essentially the same visual representation of the output. However, each level has tradeoffs for auxiliary uses, such as searching or indexing, commenting and annotation, and accessibility (text-to-speech). Keeping the running order of text in the content stream in the proper order supports all of these auxiliary uses.

In addition, the "role map" feature of PDF

(http://help.adobe.com/en_US/acrobat/X/pro/using/WS58a04a822e3e50102bd615109794195ff-7cd8.w.html) would additionally allow for the mapping of the logical tags found in the original XML into tags in the PDF.

Recommendations:

- Text in content streams should follow the XML document's logical order (in the order of tags) to the extent possible. This will provide optimal reuse by software that does not understand Tagged PDF. (PDF/UA requires this.)
- It might be possible to use the "role map" annotation to capture enough of the xml2rfc source structure, to the point where it is possible to reconstruct the XML source structure completely. However, there is not a compelling case to do so over embedding the original XML, as described in [Section 2.2.8](#).

2.2.2. Unicode Support

PDF itself does not require use of Unicode. Text is represented as a sequence of glyphs which then can be mapped to Unicode.

Recommendations:

PDF files generated must have the full text, as it appears in the original XML.

Unicode normalization may occur.

Text within SVG for SVG images should also have Unicode mappings.

Alt-text for images should also support Unicode.

2.2.3. Image Processing (Artwork)

The XML allows both ASCII art and SVG to be used for artwork.

Recommendations:

If both ASCII art and SVG are available for a picture, the SVG artwork should be the preferred over the ASCII artwork.

ASCII artwork must be rendered using a monospace font.

2.2.4. Text Description of Images (Alt-Text)

Guidelines for accessibility of PDF <http://www.w3.org/TR/WCAG20-TECHS/PDF1.html> recommend that images, formulas, and other non-text items provide textual alternatives, using the '/Alt' Tag in PDF to provide human-readable text that can be vocalized by text-to-speech technology.

Recommendation: Any alt-text for artwork and figures available in the XML source should be stored using the PDF /Alt property. Internet draft authors and the RFC editor should insure inclusion of alt-text for all SVG or images, within the XML source.

2.2.5. Metadata Support

Metadata encodes information about the document authors, the document series, date created, etc. Having this metadata within the PDF file allows it to be used by search engines, viewers and other reuse tools. PDF supports embedded metadata in a variety of ways, including using XMP [[XMP](#)], the Extensible Metadata Platform (XMP). The RFC editor maintains metadata about an RFC on its info page.

Recommendation: The PDFs generated should have all of the metadata from the XML version embedded directly as XMP metadata, including the author, date, the document series, and a URL for where the document can be retrieved. This information should be consistent with the RFC editor info page at the time of publication.

2.2.6. Document Structure Support

PDF supports an "outline" feature where sections of the document are marked; this could be used in addition

to the table of contents as a navigation aid.

The section structure of an RFC can be mapped into the PDF elements for the document structure. This will allow the bookmark feature of PDF readers to be used to quickly access sections of the document.

Recommendation: The section structure of an RFC should be mapped into the PDF elements for the document structure. This would include section headings for the boilerplate sections such as the Abstract, Status of the Document, Table of Contents, and Author Addresses, plus the obvious section headings that are normally included in the Table of Contents. If possible, this should be done in a way that the same fragment identifiers for the HTML version of the RFC will work for the PDF version.

2.2.7. Tagged PDF

NOTE: say more about the use of alternative texts for images, tagging text spans, and providing replacement texts for symbols and images. A role-map could be provided here to map the logical tags found in the RFC XML to the standard tagset for PDF. This could be included in the generated PDF. (See also <http://www.pdfa.org/2011/10/the-value-of-tagged-pdf/>.)

2.2.8. Embedded Files

PDF has the capability of including other files; the files may be labeled both by a media type and a role, the AFRelationship key [PDFA3]. In this way, the PDF file acts also as a container.

Embedded content may be compressed.

Many PDF viewers support the ability to view and extract embedded files, although this capability is not universal.

Embedding content in the PDF file allows the PDF to act as a complete package, which can be transformed, archived, and digitally signed. Useful possibilities:

- Embed the source XML input file itself within the PDF. If the source SVG and images for illustrations are also embedded, this would make the PDF file totally self-referential.

- Embed directly extractable components that are useful for independent processing, including ABNF, MIBs, source code for reference implementations. This capability might be supported through other mechanisms from the XML source files, but could also be supported within the PDF.

- Finding, extracting and embedding other components may require additional markup to clearly identify them, and additional review to insure the correctness of embedded files that are not visible.

Recommendations:

- Embed the XML source and all illustrations, for RFCs, as a standard feature for xml2rfc's PDF output.

- If possible, make this a standard feature for Internet-Drafts as well.

- Named <sourcecode> entries should be embedded.

- Embedded bitmap images (SVG sources, JPEGs, PNGs, etc) should be embedded.

2.3. Digital Signatures

PDF has supported digital signatures since PDF 1.2. There are multiple methods for signing PDF files. The signature is intended to apply not only to the bits in the file (that they haven't been modified) but also to lock down the visual presentation as well.

Normally, the authenticity of RFC files is not an issue, since the RFC editor maintains a repository of all RFCs which is widely replicated. However, the RFC Editor and staff are at times called to provide evidence that a particular RFC is the "original" and has not been visually modified, and there may be other use cases.

As signatures also apply to embedded content, embedding the XML source will provide a way of signing the source XML as well.

Recommendation: PDFs produced by the RFC editor should be signed with a PDF digital signature. The management of certificates for the RFC editor function needs further review.

Recommendation: At this time, the authors see no need for Internet-Drafts to be signed with a PDF digital signature.

3. Choosing PDF versions and Standards

PDF has gone through several revisions, primarily for the addition of features. PDF features have generally been added in a way that older viewers 'fail gracefully', but even so, the older the PDF version produced, the more legacy viewers will support that version, but the fewer features will be enabled.

As PDF has evolved a broad set of capabilities, additional standards for PDF files are applicable. These standards establish ground rules that are important for specific applications. For example PDF/X was specifically designed for Prepress digital data exchange, with careful attention to color management and printing instructions, while the PDF/E standard was designed for engineering documents.

Two additional standards families are important to the RFC format, though: long-term preservation (PDF/A), and user accessibility (PDF/UA). These then have sub-profiles (PDF/A-1, PDF/A-2, PDF/A-3), each of which have conformance levels. These standards are then supported by various software libraries and tools.

It is effective and useful to use these standards to capture PDF for RFC requirements, and they will make the PDF files useful in workflows that expect them.

Recommendations:

Use PDF 1.7; although relatively recent, it is well supported by widely available viewers.

For RFCs, require PDF/A-3 with conformance level "U". This captures the archivability and long-term stability of PDF 1.7 files, mandatory Unicode mapping, and many of the requirement features.

Use PDF/A-3 for embedding additional data (including the XML source file) in RFCs and Internet-Drafts.

Use PDF/UA.

4. References

4.1. References

[PDF] ISO, "Portable document format -- Part 1: PDF 1.7", ISO 32000-1, 2008.

Also available free from Adobe.

[XMP] ISO, "Extensible metadata platform (XMP) specification -- Part 1: Data model, serialization and core properties", ISO 16684-1, 2012.

Not available free, but there are a number of descriptive resources, e.g.,

[PDFA2] ISO, "Electronic document file format for long-term preservation -- Part 2: Use of ISO 32000-1 (PDF/A-2).", ISO 19005-2, 2011.

[PDFA3] ISO, "Electronic document file format for long-term preservation -- Part 3: Use of ISO 32000-1 with support for embedded files (PDF/A-3)", ISO 19005-3, 2012.

[PDFUA] ISO, "Electronic document file format enhancement for accessibility -- Part 1: Use of ISO 32000-1 (PDF/UA-1)", ISO 19005-3, 2012.

4.2. Informative References

- [RFC3778] Taft, E., Pravetz, J., Zilles, S. and L. Masinter, "[The application/pdf Media Type](#)", RFC 3778, May 2004.
- [RFC6949] Flanagan, H. and N. Brownlee, "[RFC Series Format Requirements and Future Development](#)", RFC 6949, May 2013.
- [I-D.flanagan-nonascii] Flanagan, H., "[The Use of Non-ASCII Characters in RFCs](#)", Internet-Draft draft-flanagan-nonascii-04, January 2015.
- [I-D.hildebrand-html-rfc] Hildebrand, J. and H. Flanagan, "[HyperText Markup Language Request For Comments Format](#)", Internet-Draft draft-hildebrand-html-rfc-04, October 2014.

Appendix A. History and Current Use of PDF with RFCs and Internet-Drafts

NOTE: this section is meant as an overview to give some background.

A.1. RFCs

The RFC series has for a long time accepted Postscript renderings of RFCs, either in addition to or instead of the text renderings of those same RFCs. These have usually been produced when there was a complicated figure or mathematics within the document. For example, consider the figures and mathematics found in RFC 1119 and RFC 1142, and compare the figures found in the text version of RFC 3550 with those in the Postscript version. The RFC editor has provided a PDF rendering of RFCs. Usually, this has been a print of the text file that does not take advantage of any of the broader PDF functionality, unless there was a Postscript version of the RFC, which would then be used by the RFC editor to generate the PDF.

A.2. Internet-Drafts

In addition to PDFs generated and published by the RFC editor, the IETF tools community has also long supported PDF for Internet-Drafts. Most RFCs start with Internet-Drafts, edited by individual authors. The Internet-Drafts submission tool at <https://datatracker.ietf.org/submit/> accepts PDF and Postscript files in addition to the (required) text submission and (currently optional) XML. If a PDF wasn't submitted for a particular version of an Internet-Draft, the tools would generate one from the Postscript, HTML, or text.

Appendix B. Tooling

This section discusses tools for viewing, comparing, creating, manipulating, transforming PDF files, including those currently in use by the RFC editor and Internet-Drafts, as well as outlining available PDF tools for various processes.

B.1. PDF Viewers

As with most file formats, PDF files are experienced through a reader or viewer of PDF files, and there are numerous viewers. One partial list of PDF viewers can be found at http://en.wikipedia.org/wiki/List_of_PDF_software#Viewers.

PDF viewers vary in capabilities, and it is important to note which PDF viewers support the features utilized in PDF RFCs and Internet-Drafts (features such as links, digital signatures, Tagged PDF and others mentioned in [Section 2](#)).

A survey of the IETF community might broaden the list of viewers in common use, but an initial list to consider include some that are currently maintained and supported viewers and legacy systems. Maintained viewers include:

Adobe Reader

Multiple platforms. Supports all of the features on most platforms.

Google Chrome

Multiple platforms. Web browser which includes PDF support. Rapidly moving target, open source.

PDF.js

Multiple platforms. A JavaScript library to convert PDF files into HTML5, usable as a web-based viewer that can be included in web browsers. Used by Mozilla Firefox. Also rapidly moving target.

Foxit Reader

Multiple platforms. PDF Viewer / Reader for Desktop computer and Mobile Devices. Recently licensed by Google, and the code for this purpose was made open source; see <http://www.i-programmer.info/news/136-open-source/7433-google-open-sources-pdf-software-library.html>.

Several "legacy" viewers to consider include: Ghostview, Xpdf.

B.2. Printers

While almost all viewers also support printing of PDF files, printing is one of the most important use cases for PDFs. Some printers have direct PDF support.

B.3. PDF Generation Libraries

Because the xml2rfc format is a unique format, software for converting XML source documents to the various formats will be needed, including PDF generation.

One promising direction is suggested in

<http://greenbytes.de/tech/webdav/rfc2629xslt/rfc2629xslt.html#output.pdf.fop>: using XSLT to generate XSL-FO which is then processed by a formatting object processor such as Apache FOP.

Several libraries are also available for generating PDF signatures.

B.4. Typefaces

This section is intended to discuss available typefaces that might satisfy requirements. Some openly available fixed-width typefaces (without extensive Unicode support, however) include: [Skolar](#), but it requires licensing. Another potentially useful set of typefaces is the [Noto](#) family from Google.

- [Source Sans](#)
- [Source Serif Pro](#)
- [Source Code Pro](#)

A font that looks promising for its broad Unicode support is

B.5. Other Tools

In addition to generating and viewing PDF, other categories of PDF tools are available and may be useful both during specification development and for published RFCs. These include tools for comparing two PDFs, checkers that could be used to validate the results of conversion, reviewing and commentary tools that attach annotations to PDF files, and digital signature creation and validation.

Validation of an arbitrary author-generated PDF file would be quite difficult; there are few PDF validation tools. However, if RFCs and Internet-Drafts are generated by conversion from XML via xml2rfc, then explicit validation of PDF and adherence to expected profiles would mainly be useful to insure that xml2rfc has functioned properly.

Recommendations:

- Discourage (but allow) submission of a PDF representation for Internet-Drafts. In most cases, the

PDF for an Internet-Draft should be produced automatically when XML is submitted, with an opportunity to verify the conversion.

Appendix C. Additional Reading

<http://www.pdflib.com/fileadmin/pdf/lib/pdf/whitepaper/Whitepaper-Technical-Introduction-to-PDFA.pdf>

http://www.pdfa.org/wp-content/uploads/2011/08/tn0003_metadata_in_pdfa-1_2008-03-128.pdf

http://www.pdfa.org/wp-content/uploads/2011/08/PDFA-in-a-Nutshell_1b.pdf

<http://www.pdfa.org/2011/08/pdfa-%E2%80%93-a-look-at-the-technical-side/> <http://pdf.editme.com/pdfa>

Appendix D. Acknowledgements

The input of the following people is gratefully acknowledged: Brian Carpenter, Chris Dearlove, Martin Duerst, Heather Flanagan, Joe Hildebrand, Duff Johnson, Leonard Rosenthol,

Authors' Addresses

Tony Hansen (editor)

AT&T Laboratories

200 Laurel Ave. South

Middletown, NJ 07748

USA

Email: tony+rfc2pdf@maillennium.att.com

Larry Masinter

Adobe

345 Park Ave

San Jose, CA 95110

USA

Email: masinter@adobe.com

URI: <http://larry.masinter.net>

Matthew Hardy

Adobe

345 Park Ave

San Jose, CA 95110

USA

Email: mahardy@adobe.com