

Relational Schema Protocol (RSP)

Internet Engineering Task Force
Internet-Draft
Intended status: Standards Track
Expires: November 29, 2011

V. Přehnal, Ed.
Faculty of Informatics
Masaryk University
May 28, 2011

Abstract

This document specifies the Relational Schema Protocol (RSP). RSP enables loosely coupled applications to share and exchange relational data. It defines fixed message format for an arbitrary relational schema so that the changes in the data schema do not affect the message format. This prevents the interacting applications from having to be reimplemented during the data schema evolvement.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>. Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress." This Internet-Draft will expire on November 29, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1	Introduction.....	3
1.1	Requirements Language.....	3
1.2	Protocol Overview.....	3
2	Data Types	3
2.1	Shared Data Types.....	3
2.1.1	TableHeader	3
2.1.2	ArrayOfTableHeader.....	4
2.1.3	ArrayOfint.....	4
2.1.4	Field	4
2.1.5	ArrayOfField.....	5
2.1.6	ArrayOfstring	5
2.1.7	ArrayOfArrayOfstring	5
2.1.8	Reference	6
2.1.9	ArrayOfReference.....	6
2.1.10	Table	6
2.2	Message Format Data Types	7
2.2.1	ReadTableHeadersRequest	7
2.2.2	ReadTableHeadersResponse	7
2.2.3	ReadTableRequest.....	7
2.2.4	ReadTableResponse	8
2.2.5	SubmitRequest	8
2.2.6	SubmitResponse	8
3	Operations.....	9
3.1	ReadTableHeaders.....	9
3.2	ReadTable.....	9
3.3	Submit	9
4	IANA Considerations.....	9
5	Security Considerations.....	9
5.1	Communication Security	9
5.2	System Security	9
6	Normative References.....	10
	Author's Address	10

1 Introduction

Widely disparate applications are very often required to share and exchange data from relational data sources. Typically, this is accomplished by passing messages over a shared environment (e.g. computer network, file system, computing memory, etc.) in a well-defined, machine-processable format. In such a case, the data schema is mapped to the message format such that the elements of the message format reflect the relations and their attributes in the data schema. If the data schema is a subject to change, the message format needs to be redefined. As a consequence, all the interacting applications need to be reimplemented. This represents a serious issue for evolving data schemas.

This specification defines a new communication protocol, RSP, for universal relational data exchange. This protocol enables the interacting applications to describe arbitrary relational schema (including the contained data) using a fixed hierarchy of data types. This way, the format of the messages does not need to be redefined when the data schema evolves.

1.1 Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

1.2 Protocol Overview

The RSP protocol defines three REQUIRED request-response operations (remote procedures) listed below:

- *ReadTableHeaders* - for data schema exploration
- *ReadTable* - for data and metadata retrieval
- *Submit* - for data manipulation (insertion, alteration, deletion)

The operation behaviors are specified in section 3. The message format of operation requests and responses is defined using the hierarchy of abstract data types in section 2. These abstract data types MAY be serialized in arbitrary serialization format (e.g. XML, JSON, etc.).

2 Data Types

This section specifies the data types used in the protocol.

2.1 Shared Data Types

This section specifies the data types shared by multiple operations.

2.1.1 TableHeader

Data type *TableHeader* represents basic metadata of particular data table. Attributes of this data type are specified in Table 1.

Name	Definition	Data Type	Multiplicity
Description	Description of the table for the documentation purposes	string	Zero or one (OPTIONAL)

PluralTitle	Plural user-friendly title of the table in the specified language	string	One (REQUIRED)
SingularTitle	Singular user-friendly title of the table in the specified language	string	One (REQUIRED)
TableName	Unique name of the table within the whole data schema	string	One (REQUIRED)

Table 1 - Attributes of the *TableHeader* data type

2.1.2 *ArrayOfTableHeader*

Data type *ArrayOfTableHeader* represents 1-dimensional list of table headers. Attributes of this data type are specified in Table 2.

Name	Definition	Data Type	Multiplicity
TableHeader	Table header (item in the list)	TableHeader, see Table 1	Zero or one (OPTIONAL)

Table 2 - Attributes of the *ArrayOfTableHeader* data type

2.1.3 *ArrayOfint*

Data type *ArrayOfint* represents 1-dimensional list of integers. Attributes of this data type are specified in Table 3.

Name	Definition	Data type	Multiplicity
int	Integer number (item in the list)	int	Zero or one (OPTIONAL)

Table 3 - Attributes of the *ArrayOfint* data type

2.1.4 *Field*

Data type *Field* represents metadata of particular table column. Attributes of this data type are specified in Table 4.

Name	Definition	Data type	Multiplicity
DataType	Data type of the column (int, varchar, datetime, ...)	string	One (REQUIRED)
Description	Description of the column for the documentation purposes	string	Zero or one (OPTIONAL)
ID	Unique identifier of the column within the whole data schema	string	One (REQUIRED)
IsAutoGenerated	True if the column is auto-generated (identity) column	boolean	One (REQUIRED)
IsDisplayField	True if the column from the joined table should be displayed instead of the foreign key column in the specified table	boolean	One (REQUIRED)
IsEditable	True if the data in the column is editable	boolean	One (REQUIRED)

IsForeignKey	True if the column is the foreign key	boolean	One (REQUIRED)
IsJoined	True if the column is a part of joined table	boolean	One (REQUIRED)
IsNullable	True if the column may contain null-values	boolean	One (REQUIRED)
IsPrimaryKey	True if the column is a part of the primary key	boolean	One (REQUIRED)
MaximumLength	Maximum character length (only for character data types)	long	Zero or one (OPTIONAL)
Name	Unique name of the column within its parent table	string	One (REQUIRED)
ReferencedField	Unique name of the referenced column within the referenced table (only for foreign key columns)	string	Zero or one (OPTIONAL)
ReferencedTable	Unique name of the referenced table (only for foreign key columns)	string	Zero or one (OPTIONAL)
Table	Name of the parent table	string	One (REQUIRED)
Title	User-friendly title of the column in the specified language	string	One (REQUIRED)

Table 4 - Attributes of the "Field" data type

2.1.5 ArrayOfField

Data type *ArrayOfField* represents 1-dimensional list of fields. Attributes of this data type are specified in Table 5.

Name	Definition	Data type	Multiplicity
Field	Field (item in the list)	Field, see Table 4	Zero or one (OPTIONAL)

Table 5 - Attributes of the *ArrayOfField* data type

2.1.6 ArrayOfstring

Data type *ArrayOfstring* represents 1-dimensional list of text strings. Attributes of this data type are specified in Table 6.

Name	Definition	Data type	Multiplicity
string	Text string (item in the list)	string	Zero or more (OPTIONAL)

Table 6 - Attributes of the *ArrayOfstring* data type

2.1.7 ArrayOfArrayOfstring

Data type *ArrayOfArrayOfstring* represents 2-dimensional list of text strings. Attributes of this data type are specified in Table 7.

Name	Definition	Data type	Multiplicity
ArrayOfstring	1-dimensional array of text	ArrayOfstring,	Zero or more (OPTIONAL)

	strings (item in the list)	see Table 6	
--	----------------------------	-------------	--

Table 7 - Attributes of the *ArrayOfArrayOfstring* data type

2.1.8 Reference

Data type *Reference* represents metadata of the referencing table. Attributes of this data type are specified in Table 8.

Name	Definition	Data type	Multiplicity
RedField	Unique name of the referenced column within the referenced table	string	One (REQUIRED)
RedTable	Unique name of the referenced table	string	One (REQUIRED)
RingField	Unique name of the referencing column within the referencing table	string	One (REQUIRED)
RingFieldTitle	User-friendly title of the referencing column in the specified language	string	One (REQUIRED)
RingTable	Unique name of the referencing table	string	One (REQUIRED)
RingTablePluralTitle	User-friendly plural title of the referencing table in the specified language	string	One (REQUIRED)

Table 8 - Attributes of the *Reference* data type

2.1.9 ArrayOfReference

Data type *ArrayOfReference* represents 1-dimensional list of references. Attributes of this data type are specified in Table 9.

Name	Definition	Data type	Multiplicity
Reference	Reference (item in the list)	Reference, see Table 8	Zero or more (OPTIONAL)

Table 9 - Attributes of the *ArrayOfReference* data type

2.1.10 Table

Data type *Table* represents data and metadata from the particular data table. Attributes of this data type are specified in Table 10.

Name	Definition	Data type	Multiplicity
Actions	List of granted permissions (actions) for the specified user and table: 1 ~ SELECT, 2 ~ INSERT, 3 ~ UPDATE, 4 ~ DELETE	ArrayOfint, see Table 3	One (REQUIRED)
Fields	List of fields (columns)	ArrayOfField, see Table 5	One (REQUIRED)
Header	Table header	TableHeader, see Table 1	One (REQUIRED)
Items	List of data items (rows)	ArrayOfArrayOfstring,	One (REQUIRED)

		see Table 7	
References	List of references (e.g. list of tables referencing specified table)	ArrayOfReference, see Table 9	One (REQUIRED)

Table 10 – Attributes of the *Table* data type

2.2 Message Format Data Types

This section specifies the data types for operation requests and responses.

2.2.1 ReadTableHeadersRequest

Data type *ReadTableHeadersRequest* defines the *ReadTableHeaders* operation request message format. Attributes of this data type are specified in Table 11.

Name	Definition	Data type	Multiplicity
UserName	User name	string	One (REQUIRED)
Password	Password	string	One (REQUIRED)
Language	Preferred localization language for the data schema (ISO 639-1 two-letter code)	string	Zero or one (OPTIONAL)

Table 11 – Attributes of the *ReadTableHeadersRequest* data type

2.2.2 ReadTableHeadersResponse

Data type *ReadTableHeadersResponse* defines the *ReadTableHeaders* operation response message format. Attributes of this data type are specified in Table 12.

Name	Definition	Data type	Multiplicity
TableHeaders	1-dimensional list of table headers	ArrayOfTableHeader, see Table 2	One (REQUIRED)

Table 12 – Attributes of the *ReadTableHeadersResponse* data type

2.2.3 ReadTableRequest

Data type *ReadTableRequest* defines the *ReadTable* operation request message format. Attributes of this data type are specified in Table 13.

Name	Definition	Data type	Multiplicity
UserName	User name	string	One (REQUIRED)
Password	Password	string	One (REQUIRED)
TableName	Unique name of the data table	string	One (REQUIRED)
Language	Preferred localization language for the data schema (ISO 639-1 two-letter code)	string	Zero or one (OPTIONAL)
Skip	Number of data items (rows) to skip	long	One (REQUIRED)
Take	Number of data items (rows) to take (if 0 is specified, all found items are returned)	long	One (REQUIRED)

OrderExpression	Defines how the data items should be sorted (ordered)	string	Zero or one (OPTIONAL)
FilterExpression	Defines how the data items should be filtered	string	Zero or one (OPTIONAL)

Table 13 - Attributes of the *ReadTableRequest* data type

2.2.4 ReadTableResponse

Data type *ReadTableResponse* defines the *ReadTable* operation response message format. Attributes of this data type are specified in Table 14.

Name	Definition	Data type	Multiplicity
Table	Data and metadata from the specified data table	Table, see Table 10	One (REQUIRED)

Table 14 - Attributes of the *ReadTableResponse* data type

2.2.5 SubmitRequest

Data type *SubmitRequest* defines the *Submit* operation request message format. Attributes of this data type are specified in Table 15.

Name	Definition	Data type	Multiplicity
UserName	User name	string	One (REQUIRED)
Password	Password	string	One (REQUIRED)
TableName	Unique name of the data table	string	One (REQUIRED)
Operation	Type of submit operation (1 ~ INSERT, 2 ~ UPDATE, 3 ~ DELETE)	int	One (REQUIRED)
Fields	List of fields	ArrayOfField, see Table 5	One (REQUIRED)
Data	Data item (table row) to submit. The order of the data values within the item must match the order of appropriate fields in Fields attribute.	ArrayOfstring, see Table 6	One (REQUIRED)

Table 15 – Attributes of the *SubmitRequest* data type

2.2.6 SubmitResponse

Data type *SubmitResponse* defines the *Submit* operation response message format. Attributes of this data type are specified in Table 16.

Name	Definition	Data type	Multiplicity
Identity	Identity of the new data item (only for INSERT operation and tables with autogenerated identity field)	String	Zero or one (OPTIONAL)

Table 16 - Attributes of the *SubmitResponse* data type

3 Operations

This section specifies the operation behaviors.

3.1 ReadTableHeaders

Operation *ReadTableHeaders* enumerates tables accessible for the specified user and returns their headers in the specified localization language. The operation request is of type *ReadTableHeadersRequest* (see Table 11). The operation response is of type *ReadTableHeadersResponse* (see Table 12).

3.2 ReadTable

Operation *ReadTable* retrieves actions (access rights for specified user), header, fields (columns), items (rows) and references of the specified table. It automatically joins all the tables referenced by foreign keys from the specified table. The operation request is of type *ReadTableRequest* (see Table 13). The operation response is of type *ReadTableResponse* (see Table 14).

3.3 Submit

Operation *Submit* inserts, updates or deletes a single data item (table row) on the side of the operation provider. The operation request is of type *SubmitRequest* (see Table 15). The operation response is of type *SubmitResponse* (see Table 16).

4 IANA Considerations

This memo includes no request to IANA.

5 Security Considerations

5.1 Communication Security

The communication security in the terms of [RFC 3552] is completely a matter of the communication environment (e.g. a transfer protocol). In order to ensure confidentiality across unsecured communication environment, the RSP messages **SHOULD** be encrypted. Furthermore, in unreliable communication environment, the data integrity **SHOULD** be verified. For these reasons, the HTTPS protocol is strongly **RECOMMENDED** as a transfer protocol for the RSP messages in the Internet environment.

5.2 System Security

The RSP protocol does not ensure full system security as specified in [RFC 3552]. It only provides a user access control in order to prevent the applications from unauthorized usage: in each operation request, the user credentials (user name and password or password hash) have to be provided by the operation requester.

The major threat regarding the system security represents inappropriate usage of the RSP-based applications, namely the SQL injection. Therefore, all the input data **SHOULD** be filtered on the side of the operation provider for the illegal characters and expressions depending upon the selected database engine.

6 Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC3552] Rescorla, E. and B. Korver, "Guidelines for Writing RFC Text on Security Considerations", BCP 72, RFC 3552, July 2003.

Author's Address

Vojtěch Přehná (editor)

Faculty of Informatics, Masaryk University
Botanicka 68a
Brno 602 00
Czech Republic

Email: xprehn@mail.muni.cz